


MXZ-2F33VF

MXZ-2F33VF2

MXZ-2F33VF3

MXZ-2F33VF4

COMBINATION TABLE



MXZ-2F33VF MXZ-2F33VF2 MXZ-2F33VF3 COOLING

Indoor units combination	Cooling capacity (kW)			Outdoor unit power consumption(kW)		Current (A)			Power factor(%)			
	Unit A	Unit B	Total			220	230	240				
15	1.50	-	1.50	-	2.90	0.360	-	0.840	1.82	1.74	1.67	90
18	1.80	-	1.80	-	4.00	0.360	-	1.120	2.02	1.93	1.85	90
20	2.00	-	2.00	-	2.90	0.360	-	0.840	2.37	2.27	2.18	90
22	2.20	-	2.20	-	4.00	0.360	-	1.120	2.53	2.42	2.31	90
25	2.50	-	2.50	-	4.20	0.360	-	1.140	2.83	2.71	2.59	90
15+15	1.20	1.20	2.40	-	3.80	0.296	-	1.106	2.63	2.51	2.41	90
15+18	1.50	1.80	3.30	-	3.80	0.279	-	1.029	4.11	3.93	3.76	90
15+20	1.28	1.72	3.00	-	3.80	0.304	-	1.104	4.38	4.19	4.01	90
15+22	1.34	1.96	3.30	-	3.80	0.279	-	1.029	4.26	4.07	3.90	90
15+25	1.24	2.06	3.30	-	3.80	0.302	-	1.102	4.37	4.18	4.01	90
18+18	1.65	1.65	3.30	-	3.80	0.252	-	0.962	3.68	3.52	3.38	90
18+20	1.56	1.74	3.30	-	3.80	0.277	-	1.027	4.25	4.06	3.89	90
18+22	1.49	1.82	3.30	-	3.80	0.302	-	1.102	4.37	4.18	4.01	90
18+25	1.38	1.92	3.30	-	3.90	0.252	-	1.002	3.68	3.52	3.38	90
20+20	1.65	1.65	3.30	-	3.80	0.302	-	1.102	4.37	4.18	4.01	90
20+22	1.57	1.73	3.30	-	3.80	0.277	-	1.027	4.25	4.06	3.89	90
20+25	1.47	1.83	3.30	-	3.80	0.277	-	1.027	4.25	4.06	3.89	90
22+22	1.65	1.65	3.30	-	3.80	0.252	-	0.962	3.68	3.52	3.38	90
22+25	1.54	1.76	3.30	-	3.90	0.252	-	1.002	3.68	3.52	3.38	90
25+25	1.65	1.65	3.30	-	4.00	0.252	-	1.042	3.68	3.52	3.38	90

MXZ-2F33VF4 COOLING

Indoor units combination	Cooling capacity (kW)			Outdoor unit power consumption(kW)	Current (A)			Power factor(%)
	Unit A	Unit B	Total		220	230	240	
15	1.50	-	1.50 - 2.90	0.360 - 0.840	1.90	1.82	1.74	86
18	1.80	-	1.80 1.60 - 4.00	0.400 - 1.120	2.11	2.02	1.94	86
20	2.00	-	2.00 1.50 - 2.90	0.470 - 0.840	2.48	2.38	2.28	86
22	2.20	-	2.20 1.60 - 4.00	0.500 - 1.120	2.64	2.53	2.42	86
25	2.50	-	2.50 1.70 - 4.20	0.560 - 1.140	2.96	2.83	2.71	86
15+15	1.20	1.20	2.40 1.10 - 3.80	0.520 - 1.106	2.75	2.63	2.52	86
15+18	1.50	1.80	3.30 1.10 - 3.80	0.813 - 1.029	4.30	4.11	3.94	86
15+20	1.28	1.72	3.00 1.10 - 3.80	0.867 - 1.104	4.58	4.38	4.20	86
15+22	1.34	1.96	3.30 1.10 - 3.80	0.843 - 1.029	4.46	4.26	4.08	86
15+25	1.24	2.06	3.30 1.10 - 3.80	0.865 - 1.102	4.57	4.37	4.19	86
18+18	1.65	1.65	3.30 1.10 - 3.80	0.729 - 0.962	3.86	3.69	3.53	86
18+20	1.56	1.74	3.30 1.10 - 3.80	0.841 - 1.027	4.44	4.25	4.07	86
18+22	1.49	1.82	3.30 1.10 - 3.80	0.865 - 1.102	4.57	4.37	4.19	86
18+25	1.38	1.92	3.30 1.10 - 3.90	0.729 - 1.002	3.86	3.69	3.53	86
20+20	1.65	1.65	3.30 1.10 - 3.80	0.865 - 1.102	4.57	4.37	4.19	86
20+22	1.57	1.73	3.30 1.10 - 3.80	0.841 - 1.027	4.44	4.25	4.07	86
20+25	1.47	1.83	3.30 1.10 - 3.80	0.841 - 1.027	4.44	4.25	4.07	86
22+22	1.65	1.65	3.30 1.10 - 3.80	0.729 - 0.962	3.86	3.69	3.53	86
22+25	1.54	1.76	3.30 1.10 - 3.90	0.729 - 1.002	3.86	3.69	3.53	86
25+25	1.65	1.65	3.30 1.10 - 4.00	0.729 - 1.042	3.86	3.69	3.53	86

MXZ-2F33VF MXZ-2F33VF2 MXZ-2F33VF3 MXZ-2F33VF4 HEATING

Indoor units combination	Heating capacity (kW)			Outdoor unit power consumption(kW)	Current (A)			Power factor(%)
	Unit A	Unit B	Total		220	230	240	
15	1.70	-	1.70 - 3.80	0.428 - 1.520	2.16	2.07	1.98	90
18	3.30	-	3.30 2.40 - 4.40	0.720 - 1.190	3.64	3.48	3.33	90
20	2.20	-	2.20 2.20 - 3.80	0.554 - 1.520	2.80	2.68	2.56	90
22	3.30	-	3.30 2.40 - 4.40	0.720 - 1.190	3.64	3.48	3.33	90
25	3.60	-	3.60 2.40 - 4.40	0.780 - 1.110	3.94	3.77	3.61	90
15+15	1.50	1.50	3.00 1.00 - 3.90	0.623 - 0.936	3.15	3.01	2.89	90
15+18	1.36	2.64	4.00 1.00 - 4.10	0.864 - 0.956	4.36	4.17	4.00	90
15+20	1.70	2.20	3.90 1.00 - 4.00	0.915 - 0.974	4.62	4.42	4.24	90
15+22	1.36	2.64	4.00 1.00 - 4.10	0.898 - 0.956	4.53	4.34	4.16	90
15+25	1.28	2.72	4.00 1.00 - 4.00	0.953 - 0.972	4.81	4.60	4.41	90
18+18	2.00	2.00	4.00 1.00 - 4.30	0.819 - 0.956	4.14	3.96	3.79	90
18+20	2.40	1.60	4.00 1.00 - 4.10	0.896 - 0.954	4.52	4.33	4.15	90
18+22	2.00	2.00	4.00 1.00 - 4.00	0.953 - 0.972	4.81	4.60	4.41	90
18+25	1.91	2.09	4.00 1.00 - 4.30	0.819 - 0.956	4.14	3.96	3.79	90
20+20	2.00	2.00	4.00 1.00 - 4.00	0.953 - 0.972	4.81	4.60	4.41	90
20+22	1.60	2.40	4.00 1.00 - 4.10	0.896 - 0.954	4.52	4.33	4.15	90
20+25	1.52	2.48	4.00 1.00 - 4.10	0.896 - 0.954	4.52	4.33	4.15	90
22+22	2.00	2.00	4.00 1.00 - 4.30	0.819 - 0.956	4.14	3.96	3.79	90
22+25	1.91	2.09	4.00 1.00 - 4.30	0.819 - 0.956	4.14	3.96	3.79	90
25+25	2.00	2.00	4.00 1.00 - 4.40	0.819 - 0.996	4.14	3.96	3.79	90

Mitsubishi Electric at your service

Mitsubishi Electric Europe B.V. Belgium Living Environment Systems

Main office

Autobaan 2 - 8210 Loppem
T 050 40 48 48 - info@mitsubishi-electric.be

Service centre

Preflexbaan 151 - 1740 Ternat
T 02 582 77 50 - service.as@mee.com

www.mitsubishi-electric.be

